

# WHEEL PAINTER

## No more bad air.


The practical painting booth for wheels and small parts.

The Wheel Painter WD 800 is a mobile extraction cabinet for simple and effective painting of small parts such as wheels, mirror housings, trims and radiator grills. No exposure to toxic paint mist.

Thanks to extraction directly on the item, the system offers maximum safety and environmental protection. It is also characterised by maximum smoothness and noise insulation.

Energy costs are drastically reduced compared to conventional extraction systems.

The WheelPainter WP 800 is ATEX certified and is suitable for Zone 2 and/or Zone 22.





## How would you like painting while breathing freely and saving energy costs?

This is no problem with the new WheelPainter WP 800 from CARTEC Autotechnik Fuchs GmbH. One hundred percent occupational safety and environmental protection are absolutely guaranteed thanks to powerful paint mist extraction directly on the item. Moreover, direct extraction of the air volume flow is much more efficient than conventional painting systems. This leads to situations where, for example,

in winter, hot air is not discharged to the outside for several minutes. This in turn has a positive effect on heating bills.

The filtered air is extracted through pipework. The separation efficiency is 99.9%. A differential pressure indicator is installed for monitoring the pre-filters and particulate filters. Filter changing is quick and easy.

The WheelPainter working height can also be adjusted. This ensures relaxed working with a back-friendly posture. **CARTEC – simply ingenious repairs.**

### Technical data: WheelPainter WP 800

Air volume flow free blowing	1400 m³/h
More effective Airflow max.	1000 m³/h
Max. stat. pressure	1500 PA
Voltage	230 V
Frequency	50/60 Hz
Motor capacity	0.75 kW
Protection class	1
IP protection class	IP 65 (motor module)
Drive type	Fan
Sound level	55 dB(A)
Weight	235 kg
Dimensions (HxWxD)	1800/800/680 mm
ATEX Zone	2(Gas) inside the booth, extraction line and 1 m around the cabinet opening
ATEX marking	EXII3GD
<b>Accessories:</b> Exhaust set	comprising wall sleeve, spiral duct, sleeve, non-return valve, reducer, PVC hose, flexible NW 160 mm, optional. Required length determined at the site.

## LESS TIME, BETTER RESULTS: PROFESSIONAL WHEEL SOLUTIONS WITH THE WHEEL MASTER SYSTEM



## WHEEL MASTER SYSTEM

